

**Amendments to the Claims**

1. (Canceled).
2. (Previously Presented) A method of mixing liquids of Claim 44 wherein said combined liquid volume of (a) is discharged into said second chamber through two or more separated capillary passageways.
3. (Previously Presented) A method of mixing liquids of Claim 2 wherein said combined liquid volume of (a) is discharged into said second chamber through at least three separated capillary passageways.
4. (Previously Presented) A method of mixing liquids of Claim 44 wherein said combined liquid volume of (a) discharged into said second chamber is discharged into at least a third chamber through one capillary passageway or via two or more separated capillary passageways.
5. (Previously Presented) A method of Claim 44 wherein said combined liquid volume of (a) is discharged into said second chamber in the form of droplets.
6. (Previously Presented) A method of Claim 44 wherein said first chamber has a volume of at least about twice that of the combined liquid volume of (a), thereby providing free space in said first chamber.

7. (Previously Presented) A method of Claim 44 wherein said second chamber has a volume of at least about twice that of the combined liquid volume of (a), thereby providing free space in said second chamber.

8. Canceled.

9. Canceled.

10. (Previously Presented) A method of Claim 44 wherein a space of at least 100  $\mu\text{m}$  is provided above the level of the combined liquid volume of (a) in the first chamber, thereby providing sufficient free space to allow liquid entering said first chamber to separate into droplets.

11. (Previously Presented) A method of Claim 44 wherein a space of at least 100  $\mu\text{m}$  is provided above the level of the combined liquid volume of (a) in the second chamber, thereby providing sufficient free space to allow liquid entering said second chamber to separate into droplets.

12.-15. (Canceled).

16. (Previously Presented) A method of Claim 3 wherein three or more separated capillary passageways are in liquid communication between said first and second chambers.

Application No.: 10/643,862

17. (Previously Presented) A method of Claim 44 wherein at least one of said first and second chambers contains steps or ramps to assist mixing of said combined liquids.

18. (Previously Presented) A method of Claim 44 wherein said combined liquid volume of (a) in said at least one capillary passageway is discharged into said second chamber with a velocity of at least 1 mm/sec.

19. (Previously Presented) A method of Claim 44 wherein said first and second liquids are dispensed from said first and second liquid wells at the same time into said first chamber through capillary passageways.

20. (Previously Presented) A method of Claim 44 further comprising moving said completely mixed combined liquid volume of (a) to downstream chambers for further processing.

21. (Canceled)

22. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein said first and second chambers are in ~~liquid~~ communication through two or more separated capillary passageways.

23. (Currently Amended) A microfluidic device of Claim 22 wherein said first and second chambers are in ~~liquid~~ communication through at least three separated capillary passageways.

24. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein said second chamber is in ~~liquid~~ communication with at least a third chamber through one capillary passageway or two or more separated capillary passageways.

25. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein said first chamber has a volume of at least about twice that of the combined volume of said first and second ~~liquid volumes~~ wells.

26. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein said second chamber has a volume of at least about twice that of the combined volume of said first and second ~~liquid volumes~~ wells.

27. Canceled.

28. Canceled.

29. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein a space of at least 100  $\mu\text{m}$  is above the level of said combined first ~~liquid~~ and second ~~liquid volumes~~ wells in the first chamber.

30. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein a space of at least 100  $\mu\text{m}$  is above the level of said combined first ~~liquid~~ and second ~~liquid~~ volumes wells in the second chamber.

31. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein said capillary passageways have cross-sectional dimensions of 1 to 2000  $\mu\text{m}$ .

32. (Previously Presented) A microfluidic device of Claim 31 wherein said capillary passageways have cross-sectional dimensions of 200 to 1000  $\mu\text{m}$ .

33. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein said capillary passageways have lengths of 0.5 to 100 mm.

34. (Previously Presented) A microfluidic device of Claim 33 wherein said capillary passageways have lengths of 1 to 50 mm.

35. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein three or more separated capillary passageways are in ~~liquid~~ communication between said first and second chambers.

36. Canceled.

37. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein at least one of said first and second chambers contains microstructures to assist mixing ~~or removal of said first and second liquids.~~

38. (Canceled).

39. (Canceled).

40. (Previously Presented) A microfluidic device of Claim 22 wherein said two or more capillary passageways have different diameters.

41. (Previously Presented) A microfluidic device of Claim 22 wherein said two or more capillary passageways are disposed so as to cause liquid streams or droplets exiting from said passageways to impinge as said liquid streams or droplets enter said second chamber.

42. (Previously Presented) A microfluidic device of Claim 22 wherein said two or more capillary passageways are manifolded before entering said second chamber.

43. (Currently Amended) A microfluidic device of Claim ~~24~~ 45 wherein said passageways have hydrophilic surfaces.

44. (Previously Presented) A method of mixing predetermined volumes of two or more liquids in a microfluidic device comprising:

(a) dispensing each of said liquids into a well determining the predetermined volume of said liquid to be mixed;

(b) discharging the predetermined volume from each of said wells through separate capillary passageways into a first chamber to begin said mixing, said first chamber having a volume greater than the sum of said predetermined volumes, thereby providing free space in said first chamber;

(c) discharging the said sum of said predetermined volumes from said first chamber into a second chamber via at least one capillary passageway to complete mixing of said predetermined volumes, said second chamber having a volume greater than said sum of said predetermined volumes, thereby providing free space in said second chamber.

45. (New) A microfluidic device in which predetermined volumes of liquids are mixed comprising:

(a) a first well having a first predetermined volume and a second well having a second predetermined volume, said wells being adapted to hold said predetermined volumes of liquids before mixing;

(b) a first chamber having a volume larger than the combined volumes said first and second wells, said first chamber being in communication with said first and second wells through separate capillary passageways;

(c) a second chamber for complete mixing of said predetermined volumes of liquids, said second chamber having a volume larger than the combined volumes of said first and second wells and in communication with said first chamber through one capillary passageway or via two or more separated passageways.